

**NEW**

**elcometer**<sup>®</sup>  
inspection equipment

# Elcometer 500

## Coating Thickness Gauge

Reliably measure up to 9mm  
of coating thickness on concrete  
& other similar substrates



- **Fast, accurate & repeatable readings**
- **Robust, ergonomic design; inspect all day, every day**
- **Can be used in accordance with ASTM D6132, SSPC PA9 & ISO 2808**
- **Field replaceable probe tips; maximise your productivity**



[www.elcometer.com](http://www.elcometer.com)

The **Elcometer 500** coating thickness gauge **accurately measures the thickness of coatings on concrete and other similar substrates\* - non destructively.**

- Accurately measure up to 9mm (355mils) of coatings on concrete or other similar substrates<sup>‡</sup>
- Easy to read, user definable display with automatic screen brightness
- Store up to 100,000 readings in up to 1,000 alpha-numeric batches
- Rugged, intelligent probes with field replaceable tips, measure up to 9mm (355mils)

C1 150 - 2,500µm (6 - 98mils)  
 C2 750 - 9,000µm (30 - 355mils)



- Measure more than 60 readings per minute in standard mode and over 140 readings per minute in scan mode
- Rugged, dust & waterproof design equivalent to IP54, ideal for almost all environments
- USB & Bluetooth® data output to PC and Android™ or iOS mobile devices
- Ergonomic design, ideal for continuous use



**STANDARDS:**  
 ASTM D6132, SSPC-PA 9,  
 ISO 2808 Method 10



\* Similar substrates include plasterboard, drywall, concrete block, brick, etc.

‡ Epoxy coatings, thickness on other materials may vary

# Coating Thickness Gauge

## Elcometer 500

### Fast

Measuring over 60 readings per minute in standard mode and over 140 readings per minute in scan mode, the Elcometer 500 coating thickness gauge can significantly reduce your inspection times.

### Reliable

The Elcometer 500 will only display the coating thickness reading if the signal strength indicator turns green, preventing false or incorrect readings.

If the coating thickness is outside the measurement range, the Elcometer 500 tells you on the display.

### Intelligent

The Elcometer 500 measurement probes are supplied with user replaceable probe tips. If the tip is damaged or wears during use you can replace it and carry on.

The gauge even informs you when you need to change the probe tip, maximising inspection time.

### Easy to Use

There is no need to set up gates, range values or know the thickness of the coating, simply select the coating material from the gauge library and start measuring.

### Ergonomic

The Elcometer 500 gauge and intelligent probes have all been ergonomically designed for continuous use. No force is required to take a reading.

### Rugged

Robust, ergonomic and sealed against dirt and water, equivalent to a rating of IP54, the Elcometer 500 has been designed to work in harsh environments, making it the ideal gauge for the laboratory or the job site.

### Powerful

The Elcometer 500 wirelessly transmits readings, statistics and batches via Bluetooth® or via USB straight into your inspection application or into Elcometer's Mobile App ElcoMaster®, for instant report generation either at your desk or in the field, using your mobile.



Large easy to read display and signal strength indicator



Ergonomic probes with replaceable probe tips



Easy to use and minimum set up required




Rugged and reliable, ideal for harsh environments



## Elcometer 500

### Create instant reports with ElcoMaster®

What you do with the collected data is just as important as taking the readings themselves.



ElcoMaster® is a fast, easy to use software solution for all your data management and quality assurance needs, preparing professional inspection reports at the click of a button.

Data transferred to ElcoMaster® includes:

- Date and time stamped readings
- Statistical values
- Limit values
- Readings above high limit
- Run charts & histograms
- Batch and gauge information
- Calibration information



ElcoMaster® Mobile App users can;

- Store live readings directly on to a mobile device and save them into batches
- View graphs in real-time whilst carrying out the inspection
- Add notes to individual batch reading
- Add photographs of the test surface to each individual batch reading at the click of a button
- Plot individual readings on to a location map, photograph or diagram via the mobile device's internal GPS
- Inspection data can be transferred from mobile to PC for further analysis and reporting
- Generate instant .pdf<sup>2</sup> report for submission



## Coating Thickness Gauge

### Connect

Connect gauge via Bluetooth® to see live readings directly on the phone and save them into batches.



### Review

Review average, maximum and minimum readings instantly.

### Manage & Print

Store all data; surface cleanliness, surface profile, climate or manual reports in easy to manage folders.

### Photos & Notes

Add photos, notes and comments.

### Image Collection

Use measurement location points on images to indicate the position for the next reading.<sup>1</sup>



### Combine

Combine different inspection parameters (such as surface profile, climate, dry film thickness) together with images, notes and other project specific information into reports.

### Collaborate

Share inspection data securely via the Cloud and collaborate on projects using the instant messaging feature in ElcoMaster®.

### Send

Email inspection data from a mobile device to a PC for further analysis and reporting or transfer data via the Cloud.



### Consistency

Stored material calibrations can be transferred to ElcoMaster®. These can be sent to any Elcometer 500 gauge, anywhere in the world.

<sup>1</sup> Android™ devices

<sup>2</sup> Available on iOS devices

## Coating Thickness Gauge

## Elcometer 500

### The different modes of calibration

The Elcometer 500's user calibration adjustment procedures are fully traceable to National and International Standards.



#### 1. Coating Material Library

The Elcometer 500's advanced measurement technology means that you no longer need to know how thick the coating should be or to set up measurement gates before taking a reading. Simply switch on the gauge, select the coating from the calibration library and take a reading - it is that easy.



#### 2. Material Thickness Calibration

To obtain the greatest measurement accuracy, the Elcometer 500 can be calibrated using the known thickness of the coating to be measured.

If a sample of known thickness is not available, the Elcometer 500 Coating Calibration Mould (CCM) can be used to create a coating of known thickness which is traceable to both National and International Standards.



#### 3. Sound Velocity Calibration

The Elcometer 500 can be calibrated by entering the speed of sound from the Product Datasheet available from the coating manufacturer.

#### Display Modes



Readings



Readings & Statistics



Readings & Run Charts



Readings & Bar Graphs



Readings & Differential

#### How to create a coating sample using the Elcometer 500 Coating Calibration Mould (CCM)



1. Place the Coating Calibration Mould (CCM) on a flat surface and completely fill the sample chamber with the test coating.



2. Using the plastic scraper, scrape over the coating allowing the excess to fall into the overflow chamber. Allow the coating to cure.



3. When fully cured, calibrate a ferrous coating thickness gauge on the side of the CCM then measure and record the dry film thickness at the centre of the coating.



4. Measure the same point using the Elcometer 500.

Enter the dry film thickness measurement and save it in the Elcometer 500's Coating Materials list.

Product Features	<input checked="" type="checkbox"/> Standard <input type="checkbox"/> Optional	
	Model B	Model T
Fast, accurate reading rate; 60+ readings per minute	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Repeatable & reproducible measurements	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Easy to use menu structure; in 30+ languages	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tough, impact, waterproof & dust resistant; equivalent to IP54	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bright colour screen; with automatic rotating display (0°, 90°, 180° & 270°)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Scratch & solvent resistant display; 2.4" (6cm) TFT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
USB power supply; via PC	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Test certificate & 2 year gauge warranty*	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ambient light sensor; with adjustable auto brightness	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Automatic probe recognition	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Gauge software updates <sup>1</sup> ; via ElcoMaster® software	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Data output	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
USB; to computer	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth®; to computer, Android™ & iOS® devices		<input checked="" type="checkbox"/>
Measurement units; µm, mm, mils, inch	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Signal strength indicator	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
User selectable reading resolution; Low & High reading resolution	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Display modes; user selectable		<input checked="" type="checkbox"/>
Readings	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Readings & differential; reading and the offset from a set nominal difference		<input checked="" type="checkbox"/>
Bar graph		<input checked="" type="checkbox"/>
Live reading trend graph; in batch mode		<input checked="" type="checkbox"/>
Run chart; trend graph of last 20 readings		<input checked="" type="checkbox"/>
User selectable statistics;	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Number of readings; $\eta$ , Mean (average); $\bar{x}$ , Standard deviation; $\sigma$ , Highest reading; $H_i$ , Lowest reading; $L_o$ , Coefficient of variation; CV%	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Nominal dry film thickness; NDFT, High & low limits; definable audible & visual alarms, Number of readings above high limit; Number of readings below low limit; Range; I		<input checked="" type="checkbox"/>
Multiple calibration methods with on-screen instructions; in 30+ languages	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Material selection; preset choice of materials or create own user defined materials	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Velocity entry; direct entry of a material's sound-velocity	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
1 Point; using a coating sample of known thickness	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Calibration lock; with optional PIN code unlock	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Gauge memory; number of readings		100,000
Number of batches; with unique batch calibrations		1,000
Alpha-numeric batch names; user definable on the gauge		<input checked="" type="checkbox"/>
Fixed batch size mode; with batch linking		<input checked="" type="checkbox"/>
Batch review graph		<input checked="" type="checkbox"/>
Delete last reading	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Limits; 40 user definable audible & visual pass/fail warnings		<input checked="" type="checkbox"/>
Live reading mode; transfer of individual readings to external device	USB	USB & Bluetooth®
Reading save function	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Date and time stamp		<input checked="" type="checkbox"/>
Scan mode		<input checked="" type="checkbox"/>
ElcoMaster® software & USB cable	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Protective case	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Plastic transit case	<input type="checkbox"/>	<input checked="" type="checkbox"/>

\* The Elcometer 500 is supplied with a one year warranty against manufacturing defects. Gauge warranty can be extended to two years via [www.elcometer.com](http://www.elcometer.com).



<sup>1</sup> Visit [www.elcometer.com/sdk](http://www.elcometer.com/sdk) to find out how to integrate Elcometer's MFi certified products to your App.

<sup>1</sup> Internet connection required

# Coating Thickness Gauge

Elcometer 500

Technical Specification <span style="float: right;">C</span>		
Part Number	Description	Certificate
A500C-B	Elcometer 500 Coating Thickness Gauge Model B	●
A500C-T	Elcometer 500 Coating Thickness Gauge Model T	●
A500-KIT1	Elcometer 500 Coatings on Concrete Inspection Kit	●
Operating Temperature	-10 to 50°C (14 to 122°F)	
Power Supply	2 x AA batteries (rechargeable batteries can be used)	
Battery Life	Alkaline: Approximately 15 hours Lithium: Approximately 28 hours	
Gauge Weight	161g (5.68oz) including batteries, without transducer	
Gauge Dimensions	141 x 73 x 37mm (5.55 x 2.87 x 1.46") without transducer	
Packing List	<p><b>Elcometer 500 Coating Thickness Gauge Model B &amp; T</b>            Elcometer 500 Coating Thickness Gauge, 4ml (0.14fl oz) bottle of probe tip oil, 120ml (4fl oz) bottle of ultrasonic couplant, 2 x AA batteries, protective case, transit case (Model T), wrist harness, 3 x screen protectors, ElcoMaster® software (Model T), USB cable (Model T), test certificate</p> <p><b>Elcometer 500 Coatings on Concrete Inspection Kit</b>            Elcometer 500 Model T Coating Thickness Gauge, C1 &amp; C2 coating thickness probes, C1 &amp; C2 probe measurement foils: 1, 2, 3 &amp; 8mm (40, 80, 120 &amp; 310mils), Elcometer 456 Model B Ferrous Integral Gauge, Elcometer 456 calibration foils: 0.5 &amp; 1.5mm (20 &amp; 60mils), 2 x coating calibration moulds, 120ml (4fl oz) bottle of ultrasonic couplant, 4ml (0.14fl oz) bottle of probe tip oil, transit case, 2 x wrist harnesses, 6 x screen protectors, ElcoMaster® software &amp; USB cable</p>	

Probe Range				
	<b>Scale C1</b>	<b>T500-C1</b>	Elcometer 500 Scale C1 Probe	Certificate
			Range <sup>1</sup> : 150 - 2,500µm (6 - 98mils) Accuracy <sup>2</sup> : ±2% or ±10µm (±2% or ±0.4mil)	●
			Resolution: Low: 10µm, 0.01mm, 1mil or 0.001" High: 1µm, 0.001mm, 0.1mil or 0.0001"	
	<b>Scale C2</b>	<b>T500-C2</b>	Elcometer 500 Scale C2 Probe	Certificate
			Range <sup>1</sup> : 750 - 9,000µm (30 - 355mils) Accuracy <sup>2</sup> : ±2% or ±10µm (±2% or ±0.4mil)	●
			Resolution: Low: 10µm, 0.01mm, 1mil or 0.001" High: 1µm, 0.001mm, 0.1mil or 0.0001"	

Accessories			
Part Number	Description	Part Number	Description
T50027602-1	C1 Replacement Probe Tip; Pack of 2	T50027602-2	C2 Replacement Probe Tip; Pack of 2
T50027604	Probe Tip Oil; 4ml (0.14fl oz) Bottle		
Part Number	Description	Part Number	Description
T92015701	Ultrasonic Couplant; 120ml (4fl oz)	T92024034-7	Ultrasonic Couplant; 300ml (10fl oz)
T92024034-8	Ultrasonic Couplant; 500ml (17fl oz)	T92024034-3	Ultrasonic Couplant; 3.8l (1 US Gallon)
T92024034-9	Ultrasonic Couplant (High Temp); 60ml (2fl oz); for use in high temperature environments up to 398°C (970°F)		
Part Number	Description	Part Number	Description
T99022255-13	C1 Foil Set: 1 & 2mm (40 & 80mils)	T99022255-13C	C1 Foil Set - Certified: 1 & 2mm (40 & 80mils)
T99022255-14	C2 Foil Set: 3 & 8mm (120 & 310mils)	T99022255-14C	C2 Foil Set - Certified: 3 & 8mm (120 & 310mils)
Part Number	Description		
T50027567-1	Elcometer 500 Coating Calibration Mould (CCM)		

● Test certificate supplied as standard

<sup>1</sup> Epoxy coatings, thickness on other materials may vary  
<sup>2</sup> Whichever is greater